

POCKET-4300

Splashproof VHF radio, portable

- 5 Watt
- All international channels
- L & F channels
- Memory of 10 channels
- Splashproof
- All channel scan, Normal and Priority Scan
- Channel 16 direct access
- Dual and Triple Watch
- Power source: Ni-Mh 7.2 V (1 400 mA)
- Battery life: over 24H on standby
- Keylock
- Charge level indicator
- Back-lighted LCD Display
- SMA Rubber Duck Antenna

Accessories

- 1 x 220V wall adapter
- 1 x Pack battery
- 1 x Dry Cell Box for 6 x LR6
- 1 x Belt clip and hand strap

Options

Cigarette lighter adapter 12V (3.012.000)
Mic-Earphone (3.012.0002)
Waterproof cover (3.015.0351)



Technical Specifications

Channels	All International Channels
Frequency Method.....	Phase Lock Loop
Frequency Range.....	TX 156.025~157.425 MHz
RX 156.300~162.000 MHz	
Antenna Impedance.....	50 Ohm
Power Supply.....	7.2VDC
Operating Temperature	-20°c to +59 °c
Dimensions (HWD) (with 7.2V Battery Pack)	148mm(H) x 60mm(W) x 39mm(D)
Weight (with 7.2V Battery Pack)	421.5g

Transmitter

Power Output.....	0.8 or 5 Watts (Switch Selectable)
Modulation Type.....	FM
Hum and Noise Attenuation	34dB
Audio	
Distortion.....	5%
Spurious	
Suppression.....	70dB

Receiver

Sensitivity at 12dB	
Sinad	0.5µV
S/N Ratio (20dB).....	0.8µV
Squelch Sensitivity.....	Threshold -12dBµV(EMF)
Adjacent Channel Rejection	70dB
Audio Power Output.....	250mW at 10% THD
Spurious Response Attenuation	70dB
Hum and Noise Attenuation	40dB
Modulation Acceptance Bandwidth	+/- 7.0KHz Minimum